Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC Supplier's address: Einkauf, Gewerbestraße 10, DE Model identifier: LED15STT10L Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type T10 (or other electric interface) Mains or non-mains: NMLS Connected light Nein source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the nearest 100 K, and the nearest 100 K, that can be set	sources							
Model identifier: LED15STT10L Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in a wide cone (120º) or in a narrow cone (90º) One mode power (Pon), 1,0 Standby power (Psb), expressed in W	Supplier's name or trade mark: DC							
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: Anti-glare shield: Product parameters Parameter Value Product parameters Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W LED Non-directional or NDLS Non-directional or ollectional or directional or directional: Non-directional or NDLS Non-directional or NDLS Non-directional or NDLS Nein Source (CLS): Only with specific dimmers Parameter Value Parameter Value General product parameters: Energy efficiency class G correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), 1,0 Standby power (Psb), expressed in W	Supplier's address: Einkauf, Gewerbestraße 10, DE							
Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Nein Non-directional: Nein Source (CLS): Only with specific dimmers Value Parameter Value General product parameters: Energy efficiency class G correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of	Model identifier: LED15STT10L							
Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Nein Envelope: - Nein Dimmable: Only with specific dimmers Value Parameter Value Parameter Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temp	Type of light sou	ırce:						
(or other electric interface) Mains or non-mains: NMLS Connected light source: Nein Envelope: - High luminance light source: Nein Anti-glare shield: Product parameters Parameter Value Parameter Value Parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Nein Envelope: - Nein Dimmable: Only with specific dimmers Value Parameter Value Parameter Value Parameter Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	Lighting technology used:		LED		NDLS			
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Nein Envelope: - Connected light source: - Nein Envelope: - Conly with specific dimmers Value Parameter Value Parameter Value Parameter Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	Light source cap-type		T10					
Source (CLS): Colour-tuneable light source: High luminance light source: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W	(or other electri	c interface)						
High luminance light source: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W	Mains or non-mains:		NMLS		Nein			
Anti-glare shield: Nein Dimmable: Only with specific dimmers	Colour-tuneable	light source:	Nein	Envelope:	-			
Parameter Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Value Parameter Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	High luminance	light source:	Nein					
Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	Anti-glare shield:		Nein	Dimmable:	· ·			
General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer 1 Energy efficiency class G Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) 90 in Sphere (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W 1,0 Standby power (Psb), expressed in W 0,00	·							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Energy efficiency Class G Standby power (Fsb), expressed in W	Parameter		Value	Parameter	Value			
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	General product parameters:							
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W	mode (kWh/1000 h), rounded up to the nearest integer		1	, ,	G			
expressed in W expressed in W	indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		(360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set				
second decimal	expressed in W		1,0	expressed in W and rounded to the	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal The provided to the nearest integer, or the range of CRIvalues that can be set	for CLS, expressed in W and rounded to the second decimal		-	index, rounded to the nearest integer, or the range of CRI- values that can be set				
OuterHeight39Spectral powerSee imagedimensionsWidth13distribution in the in last page				l ·	_			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	13	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,442			
			coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		5	Survival factor	0,90			
the lumen maintenance factor		0,50					

(a)'-': not applicable;

(b)_{'-'} : not applicable;

