Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources								
Supplier's name or trade mark: DC								
Supplier's address: Einkauf, Gewerbestraße 10, DE								
Model identifier: LED9MG4L								
Type of light source:								
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS				
Light source cap-type		G4						
(or other electri	c interface)							
Mains or non-m	ains:	NMLS	Connected light source (CLS):	Nein				
Colour-tuneable	light source:	Nein	Envelope:	-				
High luminance light source:		Nein						
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers				
Product parameters								
Parameter		Value	Parameter	Value				
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	Е				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		63 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000				
On-mode power (P _{on}), expressed in W		0,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80				
Outer dimensions	Height	30	Spectral power distribution in the	See image in last page				
ullicisions	Width	30	distribution in the	III iast hage				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	10	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,442			
			coordinates (x and y)	0,400			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		10	Survival factor	0,90			
the lumen maintenance factor		0,70					

(a)نے : not applicable;

(b)_{'-'} : not applicable;

